Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-211-6412

#### **Body Style:**

Rectangular shape

## **Overall Length:**

0.680 inches

## **Overall Width:**

0.400 inches

#### Body Height:

0.440 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Mating end

#### **Connector Locking Method:**

Detent

## End Application:

An/grc-206

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Insert Material:**

Glass single mating end and plastic polyamide single mating end

# Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

## **Terminal Type:**

Tapered pin single mating end single contact grouping

## Included Contact Quantity:

8 single mating end single contact grouping

# Included Contact Type:

Flat pin single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

## **Precious Material And Weight:**

0.008 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.