# NSN 5935-01-211-9964

**Thread Class:** 

Right-hand **Body Style:** 

**Thread Direction:** 

2b

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-211-9964

Straight shape, rectangular
Overall Length:
3.100 inches
Overall Height:
0.875 inches
Overall Width:
0.500 inches
Distance Between Mounting Facility Centers:
2.800 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
300.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping
Insert Material:
Plastic polyester single mating end

# NSN 5935-01-211-9964

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping

Feat

## **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end 1st contact grouping

**Shell Material:** 

Metal

#### **Insert Material Specification:**

Mil-m-24519, ty gpt-30f military specification single material response single mating end

#### **Included Contact Quantity:**

41 single mating end 1st contact grouping

## **Included Contact Type:**

Flat pin single mating end 1st contact grouping

## **Special Features:**

Contacts omitted at positions 2, 4, 10, 16, 17, 36, 37, 42, 44, 50 and 52

Color:

Natural

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.041 gold grains, troy

**Precious Material:** 

Gold

## **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.