

View Online at <https://aerobasegroup.com/nsn/5935-01-211-9964>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, rectangular

**Overall Length:**

3.100 inches

**Overall Height:**

0.875 inches

**Overall Width:**

0.500 inches

**Distance Between Mounting Facility Centers:**

2.800 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end 1st contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

**Insert Material:**

Plastic polyester single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping

**Criticality Code Justification:**

Feat

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end 1st contact grouping

**Shell Material:**

Metal

**Insert Material Specification:**

Mil-m-24519, ty gpt-30f military specification single material response single mating end

**Included Contact Quantity:**

41 single mating end 1st contact grouping

**Included Contact Type:**

Flat pin single mating end 1st contact grouping

**Special Features:**

Contacts omitted at positions 2, 4, 10, 16, 17, 36, 37, 42, 44, 50 and 52

**Color:**

Natural

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.041 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.