Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-1454

# Body Style:

Straight shape w/flange

## **Bushing Diameter:**

2.062 inches

## Mounting Hole Circle Radius:

1.344 inches

## **Overall Diameter:**

2.875 inches

## **Environmental Protection:**

Heat resistant and salt water resistant

## **Unthreaded Mounting Hole Diameter:**

## 0.195 inches

## **Distance From Mounting Shoulder To Rear Face:**

2.187 inches

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

3 single mating end

## **Contact Removability:**

Nonremovable single mating end all contact groupings

## **Contact Maximum Current Rating In Amps:**

30.0 single mating end all contact groupings

## Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

#### **Polarization Method:**

Contact

#### **Connector Locking Method:**

Friction

#### **Terminal Location:**

Back single mating end all contact groupings

#### **Contact Material:**

Copper alloy single mating end all contact groupings

# **Terminal Type:**

Screw single mating end all contact groupings

# Included Contact Quantity:

2 single mating end 2nd contact grouping

# Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81348-w-c-596/93 government specification

# Shelf Life:

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0