## NSN 5935-01-212-4205

**Body Style:** 

Tin

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-4205

Straight shape, external coupling Overall Length: 0.828 inches **Overall Diameter:** 0.969 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Distance From Mounting Shoulder To Front Face:** 0.411 inches **Mounting Facility Thickness:** 0.031 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-19 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Metal ferrous single mating end single contact grouping **Contact Surface Treatment:** Tin single mating end single contact grouping **Insert Material:** Glass single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Metal ferrous **Shell Surface Treatment:** 

## NSN 5935-01-212-4205

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quan	tity:
-----------------------	-------

19 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Special Features:** 

Solder flange mtd

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0