## NSN 5935-01-212-6782

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-6782 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.843 inches **Overall Height:** 1.328 inches **Overall Width:** 1.328 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.447 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-11 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 330.0 Shell Type: **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): **Thread Size:** 1.062 inches **Shell Material:** Aluminum alloy

Cadmium

**Shell Surface Treatment:** 

## NSN 5935-01-212-6782

Electrical Receptacle Connector Body - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

## **Test Data Document:**

type data in specification type data on certain etc.).

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general
environmental and performance requirements and test conditions that are shown as "typical", "average", "", e
Thread Series Designator:
Unef
Specification Data:
96906-ms27497 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.