NSN 5935-01-212-7261

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-7261
Body Style:
Straight shape, external coupling w/backshell
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Environmental Protection:
Corrosion resistant and dust resistant and fuel resistant and fungus resistant
Unthreaded Mounting Hole Diameter:
0.128 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.968 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.968 inches
Distance From Mounting Shoulder To Front Face:
0.820 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
15-19 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
End Application:
1270-01-197-8017
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

NSN 5935-01-212-7261

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0