NSN 5935-01-212-7270

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-7270 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.233 inches **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.597 inches and 0.602 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 21-11 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18

Thread Size: 1.188 inches

NSN 5935-01-212-7270

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location: |
|--|
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Criticality Code Justification: |
| Feat |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Nickel |
| Shell Surface Treatment Specification: |
| Mil-c-26074 military specification single treatment response |
| Included Contact Quantity: |
| 11 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Heavier nickel plating required for emi/rfi protection |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.011 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |