## NSN 5935-01-212-7921

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-7921
Body Style:
Straight shape, flush mount
Overall Length:
1.109 inches
Overall Height:
3.375 inches
Overall Width:
3.375 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.000 inches
Distance From Mounting Shoulder To Front Face:
0.062 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
112 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping or gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification 1st treatment response single mating end single contact grouping or mil-g-45204 military specification 2nd
treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-01-212-7921

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
112 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver or contact surfaces gold
Precious Material And Weight:
0.112 silver grains, troy or 0.112 gold grains, troy
Precious Material:
Silver or gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.