## NSN 5935-01-212-7922

Cadmium and chromate

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-212-7922

| Body Style:   |
|---|
| Straight shape  |
| Overall Length:   |
| 1.541 inches  |
| Overall Height:   |
| 0.641 inches  |
| Overall Width:  |
| 0.494 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.112 inches  |
| Distance Between Mounting Facility Centers:   |
| 1.312 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 15 single mating end  |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Polarization Method:  |
| Mating end  |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Friction  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material:  |
| Plastic polyamide single mating end   |
| Contact Surface Treatment Specification:  |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |
| Steel   |
| Shell Surface Treatment:  |

## NSN 5935-01-212-7922

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Included Contact Quantity:** 

15 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.015 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.