NSN 5935-01-213-0304

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-213-0304

Body Style:

Straight type

Overall Length:

Between 4.980 inches and 5.070 inches

Overall Height:

0.452 inches

Overall Width:

Between 0.125 inches and 0.145 inches

Environmental Protection:

Corrosion resistant and moisture resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.020 inches

Distance Between Mounting Facility Centers:

4.525 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

End Application:

An/slr-16a

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c or d military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-613, 1/2 h federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-20693, comp a, type 1 military specification single material response single mating end

NSN 5935-01-213-0304

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 48 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.048 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.