## NSN 5935-01-213-5452

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-213-5452 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.223 inches **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.602 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 95.0 Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.312 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-01-213-5452

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and nickel
Included Contact Quantity:
53 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0