

View Online at <https://aerobasegroup.com/nsn/5935-01-213-7384>

**Body Style:**

Right angle type

**Overall Length:**

2.721 inches

**Overall Height:**

0.750 inches

**Overall Width:**

0.656 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Distance Between Mounting Facility Centers:**

2.375 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

650.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-m-19833, ty gdi-30f military specification single material response single mating end

**Included Contact Quantity:**

11 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Polarizing pin located position b

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.011 gold grains, troy and 0.011 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.