

View Online at <https://aerobasegroup.com/nsn/5935-01-214-0705>

Body Style:

Straight edge type w/card guide

Overall Length:

2.760 inches

Overall Height:

1.300 inches

Overall Width:

0.360 inches

Environmental Protection:

Shock resistant and humidity resistant and fungus proof

Unthreaded Mounting Hole Diameter:

0.116 inches

Distance Between Mounting Facility Centers:

2.600 inches

Board Accommodated Length:

2.190 inches single board

Board Accommodated Width:

0.125 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Latch

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyester single mating end and glass fiber single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-24519, ty gpt-15f military specification all material responses single mating end

Included Contact Quantity:

40 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.040 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-83503/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-24519 spec.