

View Online at <https://aerobasegroup.com/nsn/5935-01-214-0705>

**Body Style:**

Straight edge type w/card guide

**Overall Length:**

2.760 inches

**Overall Height:**

1.300 inches

**Overall Width:**

0.360 inches

**Environmental Protection:**

Shock resistant and humidity resistant and fungus proof

**Unthreaded Mounting Hole Diameter:**

0.116 inches

**Distance Between Mounting Facility Centers:**

2.600 inches

**Board Accommodated Length:**

2.190 inches single board

**Board Accommodated Width:**

0.125 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Connector Locking Method:**

Latch

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyester single mating end and glass fiber single mating end

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Insert Material Specification:**

Mil-m-24519, ty gpt-15f military specification all material responses single mating end

**Included Contact Quantity:**

40 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.040 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-83503/25 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-m-24519 spec.