NSN 5935-01-214-3084

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-214-3084



Thread Class: 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.213 inches **Overall Height:** 0.621 inches **Overall Width:** 0.494 inches **Distance Between Mounting Facility Centers:** 0.984 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 9 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polyamide single mating end and glass single mating end

NSN 5935-01-214-3084

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Chromate and cadmium
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.009 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0