# NSN 5935-01-214-6875



Electrical Receptacle Connector - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/5935-01-214-6875 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.340 inches **Overall Height:** 1.562 inches **Overall Width:** 1.562 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.728 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 18.0 and 138.0 and 208.0 and 268.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi):

18 and 18

**Thread Size:** 

1.312 inches and 1.438 inches

# NSN 5935-01-214-6875

Electrical Receptacle Connector - Page 2 of 3



arm	ına	 _ocation	•
	ша	 _UCALIUII	-

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

### **Shell Surface Treatment Specification:**

Mil-c-26074, cl 3 or 4, gr b military specification single treatment response

### **Shell Material Specification:**

Qq-a-367 federal specification single material response

### **Included Contact Quantity:**

19 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.019 gold grains, troy

### **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef and unef

### **Specification Data:**

81349-mil-c-83723/82 government specification

### Shelf Life:

N/a

### **Unit Of Measure:**

### Demilitarization:

No

### Fiig:

# NSN 5935-01-214-6875

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.