NSN 5935-01-214-8538

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-214-8538 **Thread Class:** 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 31.5 millimeters **Overall Height:** 39.7 millimeters **Overall Width:** 39.7 millimeters **Unthreaded Mounting Hole Diameter:** 4.9 millimeters Center To Center Distance Between Mounting Facilities Parallel To Height: 31.7 millimeters Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 31.7 millimeters **Distance From Mounting Shoulder To Front Face:** 20.1 millimeters **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 20-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 30.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** An/sqs-t5 Thread Length: 0.219 inches

10

Thready Qty Per Inch (tpi):

NSN 5935-01-214-8538

Electrical Receptacle Connector - Page 2 of 3



Thread Size:
31.0 millimeters and 1.375 inches
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Thread Tolerance Class:
6g external
Included Contact Quantity:
79 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.079 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Iso m and special acme
Specification Data:
81349 - mil-dtl-38999/20 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

NSN 5935-01-214-8538

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0