NSN 5935-01-215-4007

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-215-4007

Thread Class: 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.938 inches **Overall Diameter:** 1.141 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 13-12 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 124.0 and 152.0 and 219.0 and 265.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring Thready Qty Per Inch (tpi): 20 and 10 **Thread Size:** 0.875 inches and 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic fluorosilicone single mating end **Criticality Code Justification:** Feat **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-01-215-4007Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium and nickel
ncluded Contact Quantity:
12 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Special Features:
20-20 socket contacts in lieu of 20-22
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and double stub
Specification Data:
31349-mil-c-28840/16 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A039b0