# NSN 5935-01-215-4020

**Thread Class:** 

**Thread Direction:** 

2a

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-215-4020



Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 3.372 inches **Overall Height:** 0.870 inches **Overall Width:** 2.592 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.468 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.280 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end and 2 polarization posts **Connector Locking Method:** Jackscrew Thready Qty Per Inch (tpi): **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass fiber single mating end

# NSN 5935-01-215-4020

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment Specification:**

Mil-g-45204, ty ii, gr d, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f or ty gdi-30f military specification all material responses single mating end

#### **Included Contact Quantity:**

117 single mating end single contact grouping

#### **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.117 gold grains, troy

#### **Precious Material:**

Gold

## **Test Data Document:**

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Unc

### **Specification Data:**

81349-mil-c-28731/31 government specification

## Shelf Life:

N/a

## Unit Of Measure:

--

## **Demilitarization:**

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.