Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-215-4268

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Rectangular shape
Overall Length:
1.680 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.375 inches
Overall Height:
0.720 inches
Overall Width:
0.750 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.093 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.500 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
75 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

NSN 5935-01-215-4268

Electrical Receptacle Connector - Page 2 of 2



Insert Material:	
	halate single mating end and glass fiber single mating end
Contact Surface	Treatment Specification:
Mil-g-45204, typ	e 1, grade c military specification single treatment response single mating end single contact grouping
Terminal Type:	
Solder well single	e mating end single contact grouping
Contact Materia	I Specification:
Qq-b-750 federa	specification single material response single mating end single contact grouping
Insert Material S	Specification:
Mil-m-14, ty gdi-3	30f military specification all material responses single mating end
Unable To Deco	de:
Unable to decode	e and unable to decode
Included Contac	et Quantity:
75 single mating	end single contact grouping
Included Contac	ct Type:
Round socket sir	gle mating end single contact grouping
Precious Materi	al And Location:
Contact surfaces	gold
Precious Materi	al And Weight:
0.075 gold grains	s, troy
Precious Materi	al:
Gold	
Thread Series D	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure	
Demilitarization	
No	
Fiig:	
A039b0	
Mil-std (military	Standard):
Mil-g-45204 spec	,