Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-215-4663

Thread Class: 2b Thread Direction: Right-hand Body Style: Straight shape, internal coupling w/strain relief Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter: 1.375 inches
Right-hand Body Style: Straight shape, internal coupling w/strain relief Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Body Style: Straight shape, internal coupling w/strain relief Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Body Style: Straight shape, internal coupling w/strain relief Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Straight shape, internal coupling w/strain relief Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Body Length: 5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
5.832 inches Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Overall Diameter: 2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
2.463 inches Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Environmental Protection: Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Corrosion resistant and shock resistant and vibration resistant Cable Entrance Diameter:
Cable Entrance Diameter:
1.373 IIICHES
Threaded Device Type:
Coupling facility
Mating End Quantity:
Contact Position Arrangement Style:
36-52 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
216.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
End Application:
An/sqs-23b
Thready Qty Per Inch (tpi):
16

NSN 5935-01-215-4663

Electrical Plug Connector - Page 2 of 2



Thread Size:
2.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0