NSN 5935-01-215-4669



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-215-4669 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 1.680 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.375 inches **Overall Height:** 0.680 inches **Overall Width:** 0.750 inches **Unthreaded Mounting Hole Diameter:** 0.093 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:**

Plastic diallyl phthalate single mating end and glass fiber single mating end

NSN 5935-01-215-4669

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty gdi-30f military specification all material responses single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.