Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-215-7933

# Thread Class: 2a Thread Direction: Right-hand Body Style: Straight shape or

Straight shape, external coupling

## Overall Length:

1.098 inches

**Overall Height:** 

0.937 inches

**Overall Width:** 

0.937 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

## **Unthreaded Mounting Hole Diameter:**

Between 0.116 inches and 0.125 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.719 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.719 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.708 inches and 0.728 inches

#### **Threaded Device Type:**

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

"10-5, 10-05" single mating end

## Contact Removability:

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

#### **Connector Locking Method:**

Externally threaded shell

## Thready Qty Per Inch (tpi):

24

## **Thread Size:**

0.688 inches



Ter	rminal Location:
Bad	ck single mating end single contact grouping
Co	ntact Material:
Me	tal ferrous single mating end single contact grouping
Co	ntact Surface Treatment:
Go	Id single mating end single contact grouping
Ins	ert Material:
Gla	ass single mating end
Co	ntact Surface Treatment Specification:
Mil	-g-45204 military specification single treatment response single mating end single contact grouping
Ter	rminal Type:
Tab	o, solder lug single mating end single contact grouping
Sh	ell Material:
Ste	el
Sh	ell Surface Treatment:
Tin	
Inc	luded Contact Quantity:
5 s	ingle mating end single contact grouping
Inc	luded Contact Type:
Ro	und pin single mating end single contact grouping
Pre	ecious Material And Location:
Co	ntact surfaces gold
Pre	ecious Material And Weight:
0.0	25 gold grains, troy
Pre	ecious Material:
Go	ld
Th	read Series Designator:
Un	ef
Sh	elf Life:
N/a	à
Un	it Of Measure:
De	militarization:
No	
Fiig	g:
A03	39b0
Mil	-std (military Standard):
Mil	-g-45204 spec.