NSN 5935-01-215-7935

Unthreaded Mounting Hole Diameter:

Body Style: Right angle type Overall Length: 2.060 inches Overall Height: 0.570 inches Overall Width: 0.360 inches

0.100 inches

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-215-7935

Distance Between Mounting Facility Centers: 1.900 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 1.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 300.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 4920-01-111-6823 **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyester single mating end and glass fiber single mating end **Terminal Type:** Solder stud single mating end single contact grouping **Insert Material Specification:** Mil-m-24519, ty gpt-15f military specification all material responses single mating end **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:**

Round pin single mating end single contact grouping

NSN 5935-01-215-7935

Mil-std (military Standard):

Mil-m-24519 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.026 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-83503/24 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0