# NSN 5935-01-216-1018

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-1018

Thread Class:
2a and 2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.350 inches
Overall Height:
0.527 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant and moisture resistant and vibration resistant
Distance Between Mounting Facility Centers:
1.150 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
End Application:
An-alr56c
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

# NSN 5935-01-216-1018

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Plastic polyphenylene single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

20 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-male and location-right hand bottomandjackscrew type-male and location-left hand top

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.020 gold grains, troy

## **Precious Material:**

Gold

#### **Thread Series Designator:**

Unc and unc and unc

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.