NSN 5935-01-216-5243

Body Style:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-5243

| Straight shape |
|--|
| Overall Length: |
| 1.020 inches |
| Overall Height: |
| 0.520 inches |
| Overall Width: |
| Between 0.070 inches and 0.080 inches |
| Environmental Protection: |
| Vibration resistant and shock resistant and salt water resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1 row of contacts non-inserted board single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 900.0 single mating end single contact grouping |
| Shell Type: |
| Solid |
| End Application: |
| 6605-01-160-4442 |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Wire wrap single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Surface Treatment: |
| Tin |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |

Included Contact Type:

Round socket single mating end single contact grouping

NSN 5935-01-216-5243Electrical Plug Connector - Page 2 of 2



| Precious Material And Location: |
|--|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0