## NSN 5935-01-216-5253

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-5253

**Body Style:** 

Straight shape threaded

**Overall Length:** 

Between 0.718 inches and 0.739 inches

**Overall Diameter:** 

Between 1.365 inches and 1.386 inches

**Distance From Mounting Shoulder To Front Face:** 

0.317 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

20-35 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Nickel single mating end single contact grouping and iron alloy 52 single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Stainless steel

**Shell Surface Treatment:** 

Tin

**Shell Surface Treatment Specification:** 

Mil-t-10727, type 1 military specification single treatment response

**Included Contact Quantity:** 

79 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-216-5253

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Solder flange mounted
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.079 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27478 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.