Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-6374

Fhread Class:	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
.659 inches	
Overall Height:	
Between 2.980 inches and 3.021 inches	
Overall Width:	
Between 2.980 inches and 3.021 inches	
Environmental Protection:	
Noisture resistant and salt water resistant and shock resistant and thermal shock resistant and vibration	n resistant
Inthreaded Mounting Hole Diameter:	
Between 0.206 inches and 0.213 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
2.375 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
2.375 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.922 inches and 0.932 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
Contact Position Arrangement Style:	
10-68 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
16.0 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
500.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
700.0 single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
nsert Position In Deg:	
30.0	
Shell Type:	
Solid	



**Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 10 Thread Size: 2.750 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end **Contact Surface Treatment Specification:** Qq-s-365 federal specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate and nickel **Included Contact Quantity:** 21 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces silver **Precious Material And Weight:** 0.105 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Double stub Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0