

View Online at <https://aerobasegroup.com/nsn/5935-01-216-6677>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.425 inches

Overall Height:

0.406 inches

Overall Width:

0.341 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

51 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Jackscrew

End Application:

5865-nc-c12-0176

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.