NSN 5935-01-216-6677

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-6677 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.425 inches **Overall Height:** 0.406 inches **Overall Width:** 0.341 inches **Environmental Protection:** Corrosion resistant and shock resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 51 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Jackscrew **End Application:** 5865-nc-c12-0176 Thready Qty Per Inch (tpi): **Thread Size:** 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic polyester single mating end

NSN 5935-01-216-6677

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, grade c, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.