# NSN 5935-01-216-6691

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-216-6691

Thread Class:
2b and 2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.350 inches
Overall Height:
0.732 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant and moisture resistant and vibration resistant
Distance Between Mounting Facility Centers:
1.150 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Gold single mating end single contact grouping

**Contact Surface Treatment:** 

# NSN 5935-01-216-6691

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

### **Included Contact Quantity:**

10 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.010 gold grains, troy

#### **Precious Material:**

Gold

## **Thread Series Designator:**

Unef and unef and unef

Shelf Life:

N/a

# **Unit Of Measure:**

\_

## **Demilitarization:**

No

# Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.