

View Online at <https://aerobasegroup.com/nsn/5935-01-216-7251>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

1.187 inches

**Overall Height:**

Between 0.682 inches and 0.692 inches

**Overall Width:**

Between 0.682 inches and 0.692 inches

**Environmental Protection:**

Shock proof and vibration proof

**Unthreaded Mounting Hole Diameter:**

0.109 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.500 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.500 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.605 inches and 0.645 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

500.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.