Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-217-0766

## Thread Class:

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape, external coupling

#### **Overall Length:**

1.405 inches

**Overall Height:** 

1.141 inches

**Overall Width:** 

1.141 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

#### Unthreaded Mounting Hole Diameter:

0.150 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

### Distance From Mounting Shoulder To Front Face:

Between 0.462 inches and 0.493 inches

#### **Threaded Device Type:**

Back shell

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

6-oct single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

90.0

## Shell Type:

Solid

#### Connector Locking Method:

Bayonet pin

#### Thread Length:

0.290 inches

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):

24

## Thread Size:

0.625 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290,

grade e federal specification 2nd treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

**Shell Material Specification:** 

Qq-a-591, a380 federal specification single material response or qq-a-367, t6 federal specification single material response

#### **Included Contact Quantity:**

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

## **Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell. Standard versions may be ordered as nsn 5935-01-179-5430, p/n m85049/52-1-10w for the straight style, or nsn 5935-01-171-5758, p/n m85049/51-1-10w for the right angle style

## Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.030 gold grains, troy

**Precious Material:** 

Gold

#### Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unef

#### **Specification Data:**

96906-ms3472 government standard

Shelf Life:

N/a

# Unit Of Measure:



**Fiig:** A039b0

Mil-std (military Standard):

Mil-g-45204 spec.