

View Online at <https://aerobasegroup.com/nsn/5935-01-217-1278>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

0.368 inches

**Overall Height:**

0.290 inches

**Overall Width:**

0.180 inches

**Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and solvent resistant and pressure proof

**Threaded Device Type:**

Mounting stud

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

454 all mating ends

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

3.000 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

900.000 all mating ends all contact groupings

**End Application:**

F-15

**Thready Qty Per Inch (tpi):**

64

**Thread Size:**

0.073 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Metal all mating ends all contact groupings

**Terminal Type:**

Crimp and solder single mating end single contact grouping

**Contact Material Specification:**

Mil-c-24308 military specification all material responses all mating ends all contact groupings

**Included Contact Type:**

Round pin all mating ends all contact groupings

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-24308 spec.