

View Online at <https://aerobasegroup.com/nsn/5935-01-217-3391>

Body Style:

Straight type

Overall Length:

3.395 inches

Overall Height:

0.670 inches

Overall Width:

0.490 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

3.075 inches

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1300.0 single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-46161, grade b, class 15 military specification single material response single mating end

Included Contact Quantity:

63 single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.063 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.