

View Online at <https://aerobasegroup.com/nsn/5935-01-217-5240>

Body Style:

Rectangular shape

Overall Length:

0.308 inches

Overall Height:

0.838 inches

Body Width:

0.200 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket center at 4 oclock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Included Contact Quantity:

2 single mating end single contact grouping

Included Contact Type:

Spring pincers single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Supplementary Features:

Mounting method - terminal

Test Data Document:

81349-mil-c-28754 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-28754/37 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.