

View Online at <https://aerobasegroup.com/nsn/5935-01-217-5249>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, external coupling

**Overall Length:**

0.700 inches

**Bushing Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.340 inches

**Overall Height:**

0.720 inches

**Overall Width:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.102 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.340 inches

**Distance From Mounting Shoulder To Rear Face:**

0.150 inches

**Flange Length:**

0.500 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Sma single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Metal

**Included Contact Quantity:**

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0