

View Online at <https://aerobasegroup.com/nsn/5935-01-217-5617>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

Between 0.709 inches and 0.724 inches

**Overall Diameter:**

0.875 inches

**Environmental Protection:**

Thermal shock resistant and vibration resistant and humidity resistant and corrosion resistant and moisture resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14s-2 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

200.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Nickel single mating end single contact grouping and iron alloy single mating end single contact grouping

**Contact Surface Treatment:**

Tin single mating end single contact grouping and cadmium single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Contact Surface Treatment Specification:**

Mil-t-10727, type 1 military specification 1st treatment response single mating end single contact grouping and qq-p-416, type 1 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Mil-i-23011, cl 2 military specification all material responses single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Tin and cadmium and copper

**Shell Surface Treatment Specification:**

Mil-t-10727, type 1 military specification 1st treatment response and qq-p-416, type 1 federal specification 2nd treatment response and mil-c-14550 military specification 3rd treatment response

**Shell Material Specification:**

Qq-s-637 federal specification single material response

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-i-23011 spec.