NSN 5935-01-217-8576

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-217-8576 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape, external coupling **Overall Length:** 0.750 inches **Bushing Diameter:** 0.162 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.340 inches **Overall Height:** 0.716 inches **Overall Width:** 0.500 inches **Environmental Protection:** Cold resistant and heat resistant and corrosion resistant and shock resistant and moisture resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.340 inches **Distance From Mounting Shoulder To Rear Face:** 0.160 inches Flange Length: 0.500 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36

Thread Size:

0.250 inches

NSN 5935-01-217-8576

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, ty ii, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Steel
Shell Material Specification:
Qq-s-764 federal specification single material response
Insert Material Specification:
L-p-403, type 1 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

A039b0

No **Fiig:**

Mil-std (military Standard):

Mil-g-45204 spec.

Demilitarization: