Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-217-8576

Thread Class:	
2b	
Thread Direction:	
Right-hand	
Body Style:	
Angle shape, external coupl	ing
Overall Length:	
0.750 inches	
Bushing Diameter:	
0.162 inches	
Center To Center Distance	Between Mounting Facilities Parallel To Length:
0.340 inches	
Overall Height:	
0.716 inches	
Overall Width:	
0.500 inches	
Environmental Protection:	
Cold resistant and heat resis	tant and corrosion resistant and shock resistant and moisture resistant
Distance Between Centerli	nes Of Mounting Facilities Parallel To Body Width:
0.340 inches	
Distance From Mounting S	houlder To Rear Face:
0.160 inches	
Flange Length:	
0.500 inches	
Threaded Device Type:	
Coupling facility	
Mating End Quantity:	
1	
Contact Position Arrangen	nent Style:
Sma single mating end	
Contact Removability:	
Nonremovable single mating	end single contact grouping
Shell Type:	
Solid	
Connector Locking Method	J:
Internally threaded coupling	nut
Radio Frequency Type Cor	ntact Characteristic Impedance In Ohms:
50.0 single mating end single	econtact grouping
Thready Qty Per Inch (tpi):	
36	
Thread Size:	
0.250 inches	

0.250 inches



## **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, ty ii, cl 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Shell Material:** Steel **Shell Material Specification:** Qq-s-764 federal specification single material response **Insert Material Specification:** L-p-403, type 1 federal specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.