## NSN 5935-01-217-8578

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-217-8578 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.125 inches **Overall Diameter:** 0.625 inches **Cable Entrance Diameter:** 0.141 inches **Distance From Mounting Shoulder To Front Face:** 0.884 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** N single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Conduit nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## NSN 5935-01-217-8578

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic fluorocarbon single mating end
Terminal Type:
Solder stud single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0