Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-217-9808

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.300 inches
Overall Height:
1.125 inches
Overall Width:
1.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
0.728 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-7 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:
0.290 inches
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### Insert Material:

Plastic single mating end

## Terminal Type:

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy 6061

## Shell Surface Treatment:

Anodize

# Included Contact Quantity:

7 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold and contact surfaces silver

# Precious Material And Weight:

 $0.025 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.025 \ \text{silver grains}, \ \text{troy}$ 

## Precious Material:

Gold and silver

# Thread Series Designator:

Unef

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0