

View Online at <https://aerobasegroup.com/nsn/5935-01-218-7936>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

1.547 inches

**Overall Diameter:**

Between 1.609 inches and 1.641 inches

**Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

**Distance From Mounting Shoulder To Front Face:**

Between 0.691 inches and 0.722 inches

**Mounting Facility Thickness:**

Between 0.062 inches and 0.125 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16-14 single mating end

**Contact Removability:**

Removable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

600.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

6920-01-142-2858

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.125 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification 1st treatment response single mating end all contact groupings and qq-n-290, grade e federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Shell Material:**

Aluminum alloy 6061

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591, a380 federal specification single material response or qq-a-367, t6 federal specification single material response

**Included Contact Quantity:**

8 single mating end 2nd contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.038 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

96906-ms3124 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.