Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-218-8324

Body Style: Right angle type **Overall Length:** 0.600 inches **Overall Width:** 0.225 inches **Body Height:** 0.310 inches **Environmental Protection:** Cold resistant and heat resistant and vibration resistant Mating End Quantity: 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 4.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 6625-01-172-5352 **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold



Precious Material And Weight:

0.006 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.