

View Online at <https://aerobasegroup.com/nsn/5935-01-219-1982>

**Body Style:**

Straight shape threaded

**Overall Length:**

1.765 inches

**Overall Diameter:**

1.750 inches

**Environmental Protection:**

Shock resistant and thermal shock resistant and moisture resistant and vibration resistant

**Distance From Mounting Shoulder To Front Face:**

0.989 inches

**Mounting Facility Thickness:**

0.125 inches

**Mating End Quantity:**

12

**Contact Position Arrangement Style:**

18-32 single mating end

**Polarization Method:**

Keyway or multiple keyway and key, multiple key groove

**Insert Position In Deg:**

0.0 and 95.0 and 132.0 and 232.0 and 260.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**End Application:**

1430-01-087-6330

**Insert Material:**

Rubber single mating end

**Shell Material:**

Aluminum alloy 6061 or aluminum alloy 380.0 or aluminum alloy a380.0

**Shell Surface Treatment:**

Nickel and copper alloy

**Shell Surface Treatment Specification:**

Mil-c-26074, class 3 or 4, grade b military specification single treatment response

**Shell Material Specification:**

Qq-a-250/11, alloy 6061, t6 federal specification single material response

**Insert Material Specification:**

Zz-r-765, class 2, grade 50-60 federal specification single material response single mating end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-26074 spec.