Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-219-9643

## **Body Style:** Right angle, card **Overall Length:** 0.435 inches **Body Width:** 0.330 inches **Body Height:** 0.238 inches **Environmental Protection:** Heat resistant and cold resistant Mating End Quantity: 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Connector Locking Method:** Friction **End Application:** 6930-nc-e19-5190 **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic phenolic single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Included Contact Quantity:** 8 single mating end single contact grouping **Included Contact Type:** Flat socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:**

0.008 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.