

View Online at <https://aerobasegroup.com/nsn/5935-01-220-6558>

Body Style:

Right angle type

Overall Length:

3.760 inches

Overall Height:

0.680 inches

Overall Width:

0.305 inches

Environmental Protection:

Cold resistant and heat resistant

Unthreaded Mounting Hole Diameter:

0.096 inches

Distance Between Mounting Facility Centers:

3.360 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

2400.0 single mating end single contact grouping

Connector Locking Method:

Latch

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Contact Material Specification:

Astm b-159 federal specification single material response single mating end single contact grouping

Included Contact Quantity:

60 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.060 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.