NSN 5935-01-221-9930

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-221-9930

Body Style:

Straight shape

Overall Height:

3.100 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

Between 0.752 inches and 0.780 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

"106, a106" all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

Mating end and 2 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends single contact grouping

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Terminal Type:

Crimp all mating ends single contact grouping

Guide Design And Location:

D shape pin left-hand at 12 oclock and d shape pin right-hand at 12 oclock

Shell Material:

Aluminum alloy

NSN 5935-01-221-9930

Electrical Receptacle Connector - Page 2 of 2



Chal	I Cur		Troot	ment:
snei	ı əur	lace	rreat	ment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Special Features:

0.188 in. Diameter hole between polarizing pins

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.212 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.