## NSN 5935-01-221-9936

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-221-9936 **Body Style:** Straight shape **Overall Length:** 0.902 inches **Overall Height:** 3.015 inches **Overall Width:** 1.330 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock proof and vibration proof **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.703 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.468 inches **Distance From Mounting Shoulder To Front Face:** 0.671 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Steel

## NSN 5935-01-221-9936

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Insert Material Specification:
Mil-m-14f military specification single material response single mating end
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14f spec.